

7.2.2 VENTILATION PIPE *with rubber insulation*

Mounting elements for smooth or spiral seamed metal and plastic pipes

- Two piece pipe clamp with welded nut on washer M8/10
- Form-fitting sound rubber insulation with an extended edge wrap-around acts as an obstruction against the unwarranted pushing out of the pipes from the clamped fitting
- In the mid section – a maximum of 18 dB (A) noise level improvement
- Using 2 locking screws* it provides a better fitting to large pipe diameter tolerances
- Locking screw as per screw dimensions – having a multi purpose cross-recess M6 and securing washer (till a nominal width of 400 mm)
- With hexagon bolt and nut M10 (from a nominal width of 450 mm onwards)
- Quick-lock (till NW 400)



Art.-Nr.	Material*	NW	Measurements	Nut	Locking screw	VPE units
547/071	Galv. steel	71	25 x 1,5	M8/10	M6 x 20	100
547/080	Galv. steel	80	25 x 1,5	M8/10	M6 x 20	100
547/090	Galv. steel	90	25 x 1,5	M8/10	M6 x 20	100
547/100	Galv. steel	100	25 x 1,5	M8/10	M6 x 20	100
547/112	Galv. steel	112	25 x 1,5	M8/10	M6 x 20	100
547/125	Galv. steel	125	25 x 1,5	M8/10	M6 x 20	100
547/140	Galv. steel	140	25 x 1,5	M8/10	M6 x 20	50
547/150	Galv. steel	150	25 x 1,5	M8/10	M6 x 20	50
547/160	Galv. steel	160	25 x 1,5	M8/10	M6 x 20	50
547/180	Galv. steel	180	25 x 1,5	M8/10	M6 x 20	50
547/200	Galv. steel	200	25 x 1,5	M8/10	M6 x 20	50
547/224	Galv. steel	224	25 x 1,5	M8/10	M6 x 20	50
547/250	Galv. steel	250	25 x 1,5	M8/10	M6 x 20	50
547/280	Galv. steel	280	25 x 1,5	M8/10	M6 x 20	50
547/300	Galv. steel	300	25 x 1,5	M8/10	M6 x 20	50
547/315	Galv. steel	315	25 x 1,5	M8/10	M6 x 20	50
547/355	Galv. steel	355	25 x 1,5	M8/10	M6 x 20	50
547/400	Galv. steel	400	25 x 1,5	M8/10	M6 x 20	50
547/450	Galv. steel	450	25 x 2,5	M8/10	M10 x 30	5
547/500	Galv. steel	500	25 x 2,5	M8/10	M10 x 30	5
547/560	Galv. steel	560	25 x 2,5	M8/10	M10 x 30	5
547/600	Galv. steel	600	25 x 2,5	M8/10	M10 x 30	5
547/630	Galv. steel	630	25 x 3,0	M8/10	M10 x 30	5
547/710	Galv. steel	710	25 x 3,0	M8/10	M10 x 30	5
547/800	Galv. steel	800	25 x 3,0	M8/10	M10 x 30	5
547/900	Galv. steel	900	25 x 3,0	M8/10	M10 x 30	1
547/1000	Galv. steel	1000	25 x 3,0	M8/10	M10 x 30	1
547/1120	Galv. steel	1120	25 x 3,0	M8/10	M10 x 30	1
547/1250	Galv. steel	1250	25 x 3,0	M8/10	M10 x 30	1

*On request available in stainless steel (E)

Stress details:

- Maximum weight till NW 400 – 600 N
- Maximum weight from NW 450 – 800 N

